IN THE CLAIMS

Please amend the claims as follows:

Claim 1 (currently amended): An evaporator comprising:

a heat exchange core comprising a plurality of tube groups arranged in rows as spaced forwardly or rearwardly of the evaporator and each comprising a plurality of heat exchange tubes arranged in parallel at a spacing laterally of the evaporator[[,]]; and

a lower tank disposed at a lower end of the core and having connected thereto lower ends of the heat exchange tubes providing the tube groups,

wherein the lower tank having has a top surface, front and rear opposite side surfaces and a bottom surface, the top surface of the lower tank is highest at an intermediate portion and is so shaped as to lower gradually from a highest portion toward the front and rear side surfaces, the highest portion of the top surface is positioned between a front heat exchange tube row and a rear heat exchange tube row of the heat exchange core, the lower tank is and being provided in each of front and rear opposite side portions thereof with front and rear grooves formed between respective laterally adjacent pairs of heat exchange tubes and extending from [[an]] the intermediate portion of the top surface with respect to [[the]] forward [[or]] and rearward direction directions to the front and rear side surfaces for causing water condensate to flow therethrough, a rear end of the front groove is positioned before a rear side of the heat exchange tubes in the front heat exchange tube row, and a front end of the rear groove is positioned behind a front side of the heat exchange tubes in the rear heat exchange tube row.

Claim 2 (original): An evaporator according to claim 1 wherein the grooves have a capillary effect to draw the condensate on the surface of the lower tank into the groove.

Claim 3 (currently amended): An evaporator according to claim 1 wherein each of the grooves includes a first portion existing on the top surface of the lower tank, and the first

portion has a bottom face gradually lowered from the intermediate inner portion in respect to the of the top surface toward a front or rear side edge thereof direction forwardly or rearwardly outward.

Claim 4 (canceled)

Claim 5 (currently amended): An evaporator according to claim [[4]] 1 wherein each of the grooves includes a first portion existing on the lower tank top surface, and the first portion has the same depth over the entire length of the first portion.

Claim 6 (withdrawn/currently amended): An evaporator according to claim [[4]] 1 wherein each of the grooves includes a first portion existing on the lower tank top surface, and the first portion has a depth gradually increasing from the highest portion side of the top surface toward the side surface.

Claim 7 (currently amended): An evaporator according to claim [[4]] 1 wherein each of the grooves includes a first portion existing on the lower tank top surface, and the first portion has a depth of 0.5 to 2.0 mm.

Claim 8 (currently amended): An evaporator according to claim [[4]] 1 wherein each of the grooves includes a first portion existing on the lower tank top surface, and the first portion has a groove width gradually increasing from a bottom of the groove toward an opening thereof.

Claim 9 (original): An evaporator according to claim 8 wherein the first portion of each groove is 0.067 to 0.33 in the ratio L1/L2 of the width L1 of the groove bottom to the width L2 of the opening.

Claim 10 (withdrawn): An evaporator according to claim 1 wherein the top surface of the lower tank is in the form of a horizontal flat surface.

Claim 11 (withdrawn): An evaporator according to claim 10 wherein each of the grooves includes a first portion existing on the lower tank top surface, and the first portion

has a groove width gradually increasing from a bottom of the groove toward an opening thereof.

Claim 12 (original): An evaporator according to claim 1 wherein each of the grooves has a flat bottom face.

Claim 13 (withdrawn): An evaporator according to claim 1 wherein each of the grooves has a bottom face shaped to a circular-arc cross section which is recessed toward a widthwise midportion of a bottom of the groove.

Claim 14 (withdrawn): An evaporator according to claim 13 wherein the bottom face of each groove has a radius of curvature which is 1/2 of the width of the groove bottom.

Claim 15 (original): An evaporator according to claim 1 wherein each of the grooves has a first portion existing on the lower tank top surface, and the ratio W2/W1 of the straight distance W2 between front and rear ends of the first portion to the entire width W1 of the lower tank in the forward or rearward direction is 0.16 to 0.47.

Claim 16 (original): An evaporator according to claim 1 wherein each of the grooves includes a second portion existing at a junction of the top surface of the lower tank and the side surface thereof, and the second portion has a bottom face inclined downward forwardly or rearwardly outward.

Claim 17 (original): An evaporator according to claim 16 wherein the bottom face of the second portion of each groove has an angle of inclination of 20 to 50 deg with a vertical plane.

Claim 18 (original): An evaporator according to claim 16 wherein each of the grooves includes a first portion existing on the top surface of the lower tank and having a bottom face, and in a longitudinal section of the groove, the bottom face of the first portion is shaped in the form of a circular arc extending from the highest portion side of the top surface of the lower tank forwardly or rearwardly outward as curved downward, the angle of

inclination of a straight line through front and rear ends of the first portion bottom face with a vertical plane being smaller than the angle of inclination of the second portion bottom face with a vertical plane.

Claim 19 (original): An evaporator according to claim 1 wherein each of the grooves includes a third portion existing on the side surface of the lower tank, and the third portion has a vertical bottom face.

Claim 20 (currently amended): An evaporator according to claim [[1]] 19 wherein each of the grooves includes a third portion existing on the side surface of the lower tank, and the third portion has a depth of 0.3 to 0.8 mm.

Claim 21 (currently amended): An evaporator according to claim [[1]] 19 wherein each of the grooves has a third portion having the same width from a bottom of the groove to an opening thereof.

Claim 22 (original): An evaporator according to claim 21 wherein the third portion of each groove has a width of 0.5 to 1.5 mm.

Claim 23 (withdrawn): An evaporator comprising a heat exchange core having a plurality of heat exchange tubes arranged laterally of the evaporator at a spacing, and a lower tank disposed at a lower end of the core and having connected thereto lower ends of the heat exchange tubes,

the lower tank having a top surface, front and rear opposite side surfaces and a bottom surface and being provided on at least one of the front and rear side surfaces thereof with a plurality of grooves extending vertically and arranged laterally of the evaporator at a spacing for causing water condensate to flow therethrough.

Claim 24 (withdrawn): An evaporator according to claim 23 wherein the grooves are formed in each of the front and rear side surfaces of the lower tank.

Claim 25 (withdrawn): An evaporator according to claim 23 wherein the entire top surface of the lower tank has a portion at least closer to each of front and rear opposite side edges thereof and lowered forwardly or rearwardly outward.

Claim 26 (withdrawn): An evaporator according to claim 23 wherein the top surface of the lower tank is highest at an intermediate portion with respect to the forward or rearward direction and is so shaped as to lower gradually from the highest portion toward a front or rear side.

Claim 27 (withdrawn): An evaporator according to claim 23 wherein the grooves have a capillary effect to draw the condensate on the surface of the lower tank into the groove.

Claim 28 (withdrawn): An evaporator according to claim 23 wherein each of the grooves has a vertical bottom face.

Claim 29 (withdrawn): An evaporator according to claim 23 wherein each of the grooves has a depth of 0.3 to 0.8 mm.

Claim 30 (withdrawn): An evaporator according to claim 23 wherein each of the grooves has the same width from a bottom of the groove to an opening thereof.

Claim 31 (withdrawn): An evaporator according to claim 30 wherein each of the grooves has a width of 0.5 to 1.5 mm.

Claim 32 (withdrawn): An evaporator according to claim 23 wherein each of the grooves has a flat bottom face.

Claim 33 (withdrawn): An evaporator according to claim 23 wherein each of the grooves has a bottom face shaped to a circular-arc cross section which is recessed toward a widthwise midportion of a bottom of the groove.

Claim 34 (withdrawn): An evaporator according to claim 33 wherein the bottom face of each groove has a radius of curvature which is 1/2 of the width of the groove bottom.

Application No. 10/563,151
Reply to Office Action of August 20, 2009

Claim 35 (previously presented): A refrigeration cycle comprising a compressor, a condenser and an evaporator, the evaporator comprising an evaporator according to claim 1.

Claim 36 (original): A vehicle having installed therein a refrigeration cycle according to claim 35 as an air conditioner.